Camara IP Tubular Wifi 2Mp IR IP66 P2P con slot SD



REFERENCIA: IP-R25-WIFI 2MP
CÓDIGO DE BARRAS -

DESCRIPCIÓN:

Cámara IP wifi de 2MP con slot para tarjeta SD. Esta cámara puede ser usada para visualizar y grabar cualquier tipo de instalación tanto en interior como en exterior. Gracias a su slot SD, esta cámara puede grabar los videos sin necesidad de un grabador externo aunque tambien puede ser usado como cámara Onvif para sitemas con grabadores NVR.

CARACTERÍSTICAS TÉCNICAS

Model NO. IPR25H200W Camera Image Sensor 1/2.9" SONY Low Illumination CMOS Sensor Resolution 2MP 1080P Effective Pixels 1985(H)*1105(V) Compression H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG TV System PAL/NTSC Electronic Shutter Time Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec S/N Ratio ?52dB Scanning System Progressive Video Output Network Reset Button NO LENS Type Focus Length Board Lens 3.6mm/F2.0 Focus Control Fixed Lens Type Fixed Pixels 3MP Night Vision Infrared LED 42µx 2PCS Infrared Distance 30M IR Status Under 10 Lux By CDS IR Power On CDS Auto Control Network Ethernet RJ-45 (10/100Base-T) Protocol TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP ONVIF Support ONVIF 2.4

P2P YES, Support QR Code POE / Video Delay 0.3S (Within the Lan) Main Stream 1 1920*1080@25fps Main Stream 2 1280*720@25fps Main Stream 3 / Sub Stream 1 720*480@25fps Sub Stream 2 / Sub Stream 3 / Tri Stream 352*288@25fps IE Brower IE8-11, Google Chrome, Firefox, Safari, Mac Safari Smart Phone iPhone, iPad, Android, Android Pad Wireless Antena 3dbi Hotspot / Wi-Fi Wi-Fi(IEEE802.11b/g/n) WIFI Range No obstacles 300m Max. Camera Features Day/Night Color/ B&W (IR-CUT) Image Config Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) Corridor Pattern / ROI / Defog Mode Support BLC Support HDR / WDR Support Motion Detection Support Privacy Masking 3 Rectangular Zone Recording Mode NVR/NAS/VMS/Web Language Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew , Italian,Nederlands, Czech Interface Audio Optional Audio in(RCA interface) Alarm / SD Card Slot support 128G Micro SD RS485 / General Housing Metal, IP66 Anti-cut Bracket Anti-Cut 3-Axis IR Cut Filter YES Operation Temperature -20? ~ +60? RH95% Max Storage Temperature -20? ~ +60? RH95% Max Power Source DC12V±10%, 500mA Dimension 157(W) x 70(H) x 66(D)mm Weight 650g

IMÁGENES EXTRAS





