

Camara IP Tubular Wifi 2Mp IR IP66 P2P con slot SD



REFERENCIA: IP-R25-WIFI 2MP

CÓDIGO DE BARRAS -



DESCRIPCIÓN:

Cámara IP wifi de 2MP con slot para tarjeta SD. Esta cámara puede ser usada para visualizar y grabar cualquier tipo de instalación tanto en interior como en exterior. Gracias a su slot SD, esta cámara puede grabar los videos sin necesidad de un grabador externo aunque tambien puede ser usado como cámara Onvif para sistemas con grabadores NVR.

CARACTERÍSTICAS TÉCNICAS

Model	NO.	IPR25H200W	Camera
Image			Sensor
	1/2.9"	SONY Low Illumination	CMOS Sensor
Resolution	2MP	1080P	Effective Pixels
	1985(H)*1105(V)		Compression
	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG		
TV System	PAL/NTSC	Electronic Shutter	Time
Auto:	PAL 1/25-1/10000Sec; NTSC 1/25-1/1000		
0Sec	S/N Ratio	?52dB	Scanning System
Progressive	Video	Output	Network
Reset Button	NO	LENS Type	Focus Length
Board Lens	3.6mm/F2.0	Focus Control	Fixed
Lens Type	Fixed	Pixels	3MP
Night Vision	Infrared LED 42μx 2PCS	Infrared Distance	30M
IR Status	Under 10 Lux	By CDS	IR Power
On CDS	Auto	Control	Network
Ethernet	RJ-45 (10/100Base-T)	Protocol	TCP/IP,ICMP,H
TTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTS			
P,RTCP,NTP,SMTP	ONVIF Support	ONVIF	2.4



P2P YES, Support QR Code POE / Video Delay 0.3S (Within the Lan) Main Stream 1 1920*1080@25fps Main Stream 2 1280*720@25fps Main Stream 3 / Sub Stream 1 720*480@25fps Sub Stream 2 / Sub Stream 3 / Tri Stream 352*288@25fps IE Brower IE8-11, Google Chrome, Firefox, Safari, Mac Safari Smart Phone iPhone, iPad, Android, Android Pad Wireless Antena 3dbi Hotspot / Wi-Fi Wi-Fi(IEEE802.11b/g/n) WIFI Range No obstacles 300m Max. Camera Features Day/Night Color/ B&W (IR-CUT) Image Config Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) Corridor Pattern / ROI / Defog Mode Support BLC Support HDR / WDR Support Motion Detection Support Privacy Masking 3 Rectangular Zone Recording Mode NVR/NAS/VMS/Web Language Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew , Italian,Nederlands, Czech Interface Audio Optional Audio in(RCA interface) Alarm / SD Card Slot support 128G Micro SD RS485 / General Housing Metal, IP66 Anti-cut Bracket Anti-Cut 3-Axis IR Cut Filter YES Operation Temperature -20? ~ +60? RH95% Max Storage Temperature -20? ~ +60? RH95% Max Power Source DC12V±10%, 500mA Dimension 157(W) x 70(H) x 66(D)mm Weight 650g

IMÁGENES EXTRAS



