

Grabador IP WIFI NVR de 4 Canales vision internet y movil



REFERENCIA:

REFERENCIA: NVR-420W

CÓDIGO DE BARRAS -

UPC: -



CARACTERÍSTICAS TÉCNICAS

Model NVR-420W System Main Processor ARM Cortex A9 Processor(HI3520D)
Operating System Embedded LINUX Video Input
9 Channel(WIFI IP Camera/Wired IP Camera), Support 1920×1080, 1280×960, 1280×720 ect
Output 1 VGA, 1 HD Audio Input / Output / Audio Bit Rate 64kbps Audio Compression standard
G.711 Alarm Sensor Input NO Output NO Motion Detection 9 Channel, MD Zones: 396 (22 × 18)
Trigger Events Recording, Email, FTP, Snapshot, Buzzer and Screen Tips Display HD Output1
resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HD Output2 / VGA
resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
Display Split 9 Channel / 4 Channel / 1Channel Digital Zoom YES OSD
Camera Title, Time, Recording, Motion Detection Recording Video Compression H.264
Resolution 1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480)
Record Rate PAL : 1080P@9×25fp, 960P@9×25fp,720P@9×25fp, D1@9×25fp
NTSC: 1080P@9×30fp, 960P@9×30fp, 720P@9×30fp, D1@9×30fp Record Mode
ManualTimerMotion Detection Playback & Backup Local Sync Playback
4CH 1080P@15fps, 2CH 1080P@30fps, 4CH 720P@30fps Decode Capability
2CH 1080P@30fps Remote Sync Playback YES Search Mode
ALL, Channel, Time, Date, Motion Detection Playback Functions
Play, Pause, Stop, Fast Play, Digital Zoom Backup Mode USB Device/Network Network

Interface 4xRJ45(1xWAN + 3xLAN) 10M/100M Adaptive Ethernet Interface Incoming Bandwidth
60MB Outgoing Bandwidth / Network Functions
TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
Onvif Version Support Onvif 2.4 Web Browser
IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53) CMS Software
Support Windows 7/ Windows 8/Windows 10 Cloud Support(P2P) Yes Smart Phone
iPhone, iPad, Android, Android PAD POE / WIFI Support, WIFI Range: No Obstacles 300m Max.
Storage Interface Type 1 SATA Interface Capacity Up to 6TB capacity eSATA / General
Language Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa
German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Gre
ek USB Interface 2 USB 2.0 Interfaces RS485 / Power Supply DC12V/2A Working Environment
-10~55°/10~90% Dimension(W×D×H) 219*217*40(mm) Weight 2.0KG (without HDD)